

Training Information

HOW TO HIGH SPEED RESTORE A FLOOR

Tools & Materials Needed:

- A. Finish mop
- B. Mop bucket with wringer
- C. Liner
- D. High speed machine
- E. Pads
- F. "Wet floor" signs
- G. Products
- H. Gloves and glasses

Products:

Floor finish restorer

Procedures:

I. Purpose of High Speed Restoration

- A. Restore luster to floor dulled by heavy foot traffic.
- B. Give the floor the "wet look".
- C. Used between recoating and stripping to fill in scratches.

II. Procedure for High Speed Restoration

- A. Allow floor to dry thoroughly after damp mopping.
- B. Line an empty mop bucket with a liner. Put on gloves and glasses.
- C. Mix floor finish restorer with water according to manufacturer's directions.
- D. Place or keep "Wet floor" signs at each entrance.
- E. Dip a clean finish mop into the floor finish restorer and wring out dry enough so it does not drip.
- F. Apply a thin coat of floor restorer
 1. Start in farthest corner from the entrance.
 2. Apply in figure eight motion, in 6 to 8 foot sections.
 3. Turn mop head over frequently.
- G. Allow to dry while cleaning up equipment.

1. Clean out finish mop.
2. Discard any floor finish restorer remaining in bucket. Twist, tie and toss.
 - H. Dry buff the floor finish restorer on the floor using a high speed machine with the appropriate pad.
 - I. After polishing floor, wash out pads. Store all equipment away for future use.